

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
31 March 2005 (31.03.2005)

PCT

(10) International Publication Number
WO 2005/028009 A1

(51) International Patent Classification⁷: **A61M 16/06**

(72) Inventor; and

(21) International Application Number:
PCT/AU2004/001309

(75) Inventor/Applicant (*for US only*): **KWOK, Philip, Rodney** [AU/AU]; 15 Davies Street, Chatswood, New South Wales 2067 (AU).

(22) International Filing Date:
24 September 2004 (24.09.2004)

(74) Agents: **DAVIDSON, Geoffrey, Robert et al.**; 1 Market Street, Sydney, New South Wales 2000 (AU).

(25) Filing Language: English

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(26) Publication Language: English

(30) Priority Data:
60/505,718 25 September 2003 (25.09.2003) US

(71) Applicant (*for all designated States except US*): **RESMED LIMITED** [AU/AU]; 97 Waterloo Road, North Ryde, New South Wales 2113 (AU).

[Continued on next page]

(54) Title: VENTILATOR MASK AND SYSTEM



(57) Abstract: A continuous positive air pressure ("CPAP") or ventilator system includes a mask (60) and an air flow generator (20). The air flow generator is mounted or provided to the mask's wearer. In one embodiment, air flow generator is mounted on the mask.

WO 2005/028009 A1



(84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*

VENTILATOR MASK AND SYSTEM

CROSS-REFERENCE TO PRIORITY APPLICATION

[0001] This application claims the benefit of U.S. Provisional Application No. 60/505,718, filed September 25, 2003, the content of which is incorporated herein by reference in its entirety.

BACKGROUND OF THE INVENTION

1. Field of The Invention

[0002] The present invention relates to ventilators, e.g., continuous positive air pressure ("CPAP") systems comprising a mask and an air flow generator, wherein the air flow generator is mountable to the mask's wearer. In one embodiment, the present invention provides CPAP systems wherein an air flow generator is mounted on the mask. In other embodiments, the air flow generator may be provided to the body of the wearer, e.g., the arm, leg, chest or waist, and a short air delivery tube can be used to connect the mask with the air flow generator.

2. Description of Related Art

[0003] CPAP administration is commonly used to treat respiratory conditions such as obstructive sleep apnea. The procedure for CPAP administration typically involves sealingly engaging a mask over a patient's nasal and/or oral region and supplying pressurized air to a chamber formed by the interior of the mask. In conventional systems, the air is supplied to the mask by an air flow generator typically placed in proximity to the patient's bed. An air delivery tube is thus needed to deliver air generated by the air flow generator to the mask.

[0004] There are two main sources of instability of a mask system during use or sleep. Normal patient movement can create instability, for example, a patient rolling on his or her side, which may cause the mask to interfere with the bedding material. Another concern of using an air delivery tube that is connected to an apparatus away from the patient is so-called "tubing drag", which refers to a drag force on the air delivery tube which is draped over the back or side of the bed. Tubing drag can be created or complicated by movement of the wearer. Tubing drag may cause relative movement between the mask seal and the patient's face during the CPAP administration and produce leaks and/or discomfort.

[0005] Another concern involving the air delivery tube is the length thereof (often about 2 meters or more), which may impart a lag in the response and rise times in delivering pressured air from the air flow generator to the mask. Increased flow impedance and/or pressure drop due to diameter and length of tubing may also necessitate a larger blower motor to compensate for the pressure drop along the air delivery tube.

[0006] U.S. Patents 4,590,951; 5,372,130; and 6,435,184 describe masks for safety applications.

SUMMARY OF THE INVENTION

[0007] Aspects of the present invention include addressing the concerns in the art, e.g., by reducing or eliminating the risk of tubing drag during CPAP administration.

[0008] A further aspect of the present invention is to provide the wearer with a greater freedom of movement in bed without compromising seal and/or comfort.

[0009] Another aspect of the present invention includes reducing or eliminating the lag in response/rise times in delivering pressured air from the generator to the mask.

[0010] In one embodiment, a ventilator or CPAP system comprises a mask and an air flow generator, wherein both the mask and the air flow generator are provided to or on the wearer. In one embodiment, the mask is configured to be fitted to the patient's face and the air flow generator is mountable to the wearer's body. The air flow generator may be provided directly to the mask.

[0011] According to one embodiment a CPAP system comprises a face mask and an air flow generator, wherein the air flow generator is mounted on the face mask.

[0012] In a further embodiment, a ventilator or CPAP system comprises:

- (i) a face mask configured to be placed over an area of a wearer's face, the face mask having:
 - (1) a shell;
 - (2) a cushion provided to a perimeter of the shell to sealingly connect the face mask to the area of a wearer's face and thereby form a chamber between the shell and the wearer's face; and
 - (3) an inlet port in the shell to receive a flow of breathable gas;
- (ii) an air flow generator, said air flow generator being mounted on said mask and being capable of creating a pressure of about 2-40cm H₂O in the chamber.

[0013] In embodiments, a ventilator or CPAP system includes an air flow generator able to be located sufficiently close to a wearer so that an air delivery tube may be less than 1.5 meters in length.

[0014] In one embodiment, a ventilator or CPAP system comprises:

a face mask having an inlet port,
an air flow generator having an outlet, and
at least one air delivery tube for delivering breathable gas from the gas outlet to the inlet port,

wherein the at least one air delivery tube does not exceed about 1.5 meters in length. The at least one air delivery tube may include two or more air delivery tubes having a combined overall length of not more than about 1.5 meters.

[0015] In a further embodiment, a ventilator or CPAP system comprises:

- (i) a face mask having
 - (1) a shell;
 - (2) a cushion provided to the shell to sealingly connect the face mask to a wearer's face and thereby form a chamber between the shell and the wearer's face, and;
 - (3) an air inlet port in the shell to receive a flow of breathable gas;
- (ii) an air flow generator; and
- (iii) an air delivery tube not exceeding 1.5 meters in length, the air delivery tube being functionally connected to the air inlet port and the air flow generator to create a pressure of about 2-40cm H₂O in the chamber by delivery of breathable gas from the air flow generator to the air inlet port.

[0016] Additional aspects, advantages and features of the present invention are set forth in this specification, and in part will become apparent to those skilled in the art on examination of the following, or may be learned by practice of the invention. The inventions disclosed in this application are not limited to any particular set of or combination of aspects, advantages and features. It is contemplated that various combinations of the stated aspects, advantages and features make up the inventions disclosed in this application.

BRIEF DESCRIPTION OF THE DRAWINGS

[0017] Figure 1 is a perspective view of a CPAP system according to one embodiment of the invention;

[0018] Figure 2 is an exploded view of the CPAP system of Figure 1;

[0019] Figure 3 is a front view taken from an interior of the CPAP system of Figure 1;

[0020] Figure 4 is a rear view taken from an exterior of the CPAP system of Figure 1;

[0021] Figure 5 is a right side view of the CPAP system of Figure 4;

[0022] Figure 6 is a top view of the CPAP system of Figure 4;

[0023] Figure 7 is a bottom view of the CPAP system of Figure 4;

[0024] Figure 8 is a bottom view of a CPAP system according to a further embodiment of the invention;

[0025] Figure 9A illustrates a person wearing the CPAP system of Figure 1;

[0026] Figure 9B illustrates an alternative embodiment of the present invention;

[0027] Figure 10A illustrates a person wearing a CPAP system according to a further embodiment of the invention;

[0028] Figure 10B is a schematic view of an air flow generator and battery pack for a CPAP system according to an embodiment of the invention;

[0029] Figure 11A represents a person wearing a person wearing a CPAP system according to a further embodiment of the invention; and

[0030] Figure 11B represents a battery pack and strap for a CPAP system according to an embodiment of the invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

[0031] A CPAP system includes a mask and an air flow generator, wherein the air flow generator is provided to a wearer of the mask. In one embodiment, the air flow generator is mountable to a wearer's body (including a wearer's clothing). In another embodiment, the air flow generator is mounted on or provided to the mask.

[0032] Figures 1-11B show several embodiments of CPAP systems according to the present invention.

[0033] Referring to Figure 1, a CPAP system 10 includes a mask 60 provided with a cushion 30 and a shell 46 to form an air chamber in communication with the airways of a wearer. In this example, the mask 60 covers at least the oral and nasal region of a wearer. However, the mask 60 could also be a nasal mask and cover, for instance, only the nasal region or only the mouth region. In either case, it is preferable that the mask does not cover or interfere with the wearer's eyes or vision. The mask may include a vent opening 61 for CO₂ gas washout, and one or more inlet

ports 47 for use in introducing supplemental gas, e.g., oxygen, into the air chamber.

The vent opening 61 can be covered with a suitable insert 63 or the like to controllably exhaust CO₂. The insert is described in ResMed's U.S. Patent Nos. 6,561,190 and 6,561,191, each incorporated herein by reference in its entirety.

[0034] Mask cushion 30 is preferably made of a soft material (e.g. a rubber material, such as a silicone elastomer) and sealingly connects to the wearer's face to form the air chamber between the wearer's face and the mask 60. The shell can be made of a relatively hard plastic, although the shell can be made of the same material as the cushion 30, in some applications. Examples of cushions 30 are described in, for instance, U.S. Patent 6,513,526, assigned to ResMed Limited, which is hereby incorporated in its entirety by reference. Commercial examples of mask 60 include, for instance, the Mirage® Full Face Mask Series II from ResMed Limited (not taking into account adjustments described below in more detail).

[0035] Headgear connectors 50 are provided to the shell 46. Headgear connectors are designed to receive headgear straps for securing CPAP system 10 to a wearer's head (securing straps 55 are shown in Figures 9 and 10A). Attached to shell 46 is an extension 72 which will generally be provided with a resilient pad (not shown) to engage the forehead of the wearer, to provide additional stability. A strap may be provided to each connector 50 of the extension 72 for contact with the wearer's crown. Alternatively, or in addition, a strap connector 50a may be provided to the extension 72 such that the strap extends over the top of the wearer's head, as shown in Figures 9 and 10A.

[0036] The air chamber formed between a wearer's face and the interior of mask 60 receives breathable gas (e.g. air) through air inlet port 56 (see Figure 2), which is designed to be placed in close proximity to (e.g. over) the wearer's oral/nasal region. The breathable gas is supplied by air flow generator 20. In one embodiment, the air flow supplied by air flow generator 20 creates single or variable pressures within the air chamber in the range of 2-40 cm H₂O, for instance 10-28 cm H₂O or 15-20 cm H₂O; or relatively constant 10 cm H₂O etc.

[0037] Referring to Figure 2, air flow generator 20 includes, for example, a first part 90 and a second part 80 that are joined, e.g., by screws 130 through bores 134 and 136 to form a housing for impeller 120 and motor 100. The parts 80 and 90 may be made from a variety of materials, for instance from cured resinous materials, from metal (e.g. aluminum), or from polymers, e.g. from polyolefins (such as polyethylene or polypropylene), polycarbonates, or acrylonitrile-butadiene-styrene polymers ("ABS").

[0038] Motor 100 drives impeller 120. Power is supplied to motor 100 via power cord 110 and the motor is fixedly secured within the impeller housing by tightening screw 132. Examples of electrical motors include, for instance, miniature bullet motors commercially available from, e.g., Servo Magnetics Inc., of California. However, various types of motors may be used, including for instance pneumatic air powered motors in which case the energy source would be a tiny air line instead of an electrical pulse. The motor assembly may include multiple motors or single motors with multiple impellers, double ended impellers, etc. Other possibilities include separate systems which can deliver prescribed air pressure. In another variant,

another motor impeller assembly can be utilized to modify, for instance, if an inflatable cuff is provided to react to stimulus or sensed parameters like leak problems. A separate motor impeller can be used to control positioning of the mask relative to the face or the profile of the cushion seal.

[0039] Examples of impellers include, for instance, the S6 CPAP impeller from ResMed Limited. Various impellers may be used, however, such as axial fans, radial fans, centrifugal fans, etc. or any new technology able to deliver the required flow of gas such as air.

[0040] The power cord 110 may receive power from any suitable power source, e.g., a wall power outlet, wall mounted transformers, a battery pack or other power storage medium. In one embodiment, power cord 110 includes sensor cables to register and/or adjust to data received from sensors that may be provided in the mask (e.g. CO₂, O₂, humidity, pressure, flow, and/or temperature sensors). In one embodiment, the monitoring of sensors occurs via infrared technology or radio waves. A control box may be provided to adjust, e.g., the motor speed, e.g., for bi-level treatment, or other parameters relative to the information received through the sensors. Other embodiments may be to sense leak and adjust motor speed and thus delivery pressure or flow accordingly.

[0041] The power cord 110 can be connected to a small controller chip (not shown) integrated with an electrical transformer plugged into a power outlet. This provides greater flexibility, freedom of movement of the wearer, increased versatility during traveling, etc. Also, there are less components at the mask interface, less overall size of the system and potentially greater stability. The system may be used

for bi-level treatment or general ventilatory applications, e.g., where the magnitude of the pressurized air varies. The system may also provide faster response and rise times and eliminate or at least reduce lag associated with air delivery tubes typically having a length of 2m or more. The system may be easier to use from the perspective of a physician, a dealer or clinician, in that only one rather than numerous components need to be fitted for the wearer.

[0042] Another embodiment provides the ability to change the strap adjusting points; the ability to modify the fit of the mask relative to the face through the integrated sensing. For example, if there is a leak generated by the mask and a sensor, e.g., a pressure transducer 67 (Figure 4), produces a signal indicative of leaking in the mask, the flow generator pressure could be modified. There is also an embodiment where bladders or cuffs or sections of the mask seal could be modified so that the seal profile is modified in certain regions until the leak is resolved and the sensors would provide feedback to the control box that the leak is gone and the motor can be controlled to react to the feedback. See, e.g., U.S. Patent Application No. 10/332,578 filed December 19, 2002, to ResMed, incorporated herein by reference in its entirety.

[0043] Sensing flow or pressure of the mask system will increase reaction time and having a motor and an impeller assembly mounted directly into a mask system would mean that reaction times to pressure and flow changes would be very rapid; therefore there is improved synchrony of delivered gas to the wearer. Presently, flow generators essentially need to predict when a patient is about to breathe in or have some delay or lag, for example, by pressure sensors mounted to the flow generator. By contrast, one aspect of the present embodiment allows the mask system to react

very quickly, which provides excellent synchrony of the flow to a patient and this is key to treat patients especially those with respiratory insufficiency who require very good synchrony of flow generator flow pattern to a breathing patient.

[0044] Air flow generator 20, e.g., second part 80, is mounted on mask 60, e.g., with four screws 140 (only two are shown in Figure 2) which extend through holes 70 (also, only two shown) into bores 136 (at the opposite side of screws 130). Of course, a variety of other methods for mounting the air flow generator 20 on full face mask 60 are feasible, such as using adhesives, using melt-welding, or integrally forming the shell 46 and second part 80 through injection molding. Still another embodiment includes the ability to easily remove the generator 20 from the mask, e.g., to facilitate cleaning, etc. One or more quick release clips could be used for this purpose.

[0045] In one embodiment, such as the embodiment shown in Figure 2, a perforated screen 40 (e.g. a perforated metal screen, for instance a perforated aluminum screen) is placed between inlet port 56 and air flow generator 20. The screen separates the outlet 85 (Fig. 3) from air flow generator 20 and prevents foreign matter that might enter the air flow generator from reaching the wearer's oral and facial region (air outlet 85 is visible in Figure 3 through screen 40). Perforated screen 40 also ensures that a wearer's tongue or other body parts larger than perforation size cannot contact the impeller 120. Examples of perforated screen 40 include, for instance, a mesh structure or a thin plate with a plurality of small bores. This arrangement also prevents any motor or impeller failure such as breakage from harming the wearer.

[0046] Figures 3-7 show various views for the CPAP mask 10 in Figures 1 and 2. A further embodiment is depicted in Figure 8, where a filter 128 is provided in front of air intake opening 125 (See Figure 7 for air intake opening 125). The filter 128 may be, for instance, a filter to prevent dust from entering the impeller system (i.e. a dust filter) or a perforated screen. Although a perforated screen does not prevent dust from entering the impeller system, it is helpful in avoiding, for instance, the wearer's fingers from being able to come into contact with the impeller 120. In addition, a perforated screen prevents larger particles from entering the impeller system. In one embodiment, the CPAP system and/or the air flow generator has a dust or antimicrobial filter. In a further embodiment, the CPAP system and/or air flow generator is absent a dust or antimicrobial filter.

[0047] Referring to Figure 9A, the CPAP system of Figure 1 is mounted on the face of a wearer 1 by means of strap 55. The power is provided to the air flow generator 20 by battery pack 150 via power cord 110. Battery pack 150 is attached to the wearer's body via strap 160. Advantages of using a battery pack as the power source include, for instance, the increased mobility of the wearer. In yet another embodiment illustrated in Figure 9B, power to the air flow generator may be provided via a transformer power pack 150' plugged into a wall outlet 163.

[0048] Figure 10A shows an embodiment where impeller system 20A is not directly mounted on mask 60A but instead on a wearer's body via strap 160. The air outlet of air flow generator 20A is attached to air delivery tube 65, which is connected to the air inlet port of full face mask 60A via socket 64 and coupling tube 62. In one embodiment, air delivery tube 65 is shorter than 1.5 meter, for instance 1.0 meter or

0.5 meter. The air delivery tube may be of any diameter or include multiple air tubes that are low profile and/or kink resistant, as described in ResMed's U.S. Patent Application No. 60/494,119 filed August 12, 2003, incorporated by reference in its entirety. Power is supplied to air flow generator 20A by battery pack 150 via power cord 110A. Power pack or flow generator may also be integrated into one assembly.

[0049] In one embodiment, air flow generator 20A and battery pack 150 are attached to strap 160 using clips 162A and 162B (see Figure 10B). Of course, this embodiment is not limited to such an attachment system and the air flow generator and/or battery pack may be attached to any suitable part of a wearer's body (including clothing) by any suitable means. For instance, as depicted in Figures 11A and 11B, air flow generator 20A may also be attached to a wearer's arm using, e.g., a Velcro® strap 160A. The motor assembly, including the impeller, may also be attached to other portions of the wearer's body, e.g., the chest via a strap, the shoulder, etc.

[0050] In yet another variant (not shown), the motor assembly may be mounted or provided or combined to a headgear system, with short tubing running to the mask. The headgear system could act as form a of vibration damping. Motors invariably vibrate due to imbalances or during motion. Isolating this vibration from the wearer will reduce irritation and noise. As the head is sensitive to vibration, some form of motor and/or impeller isolation is preferable. A damping system may be used; for example a visco-elastic/soft foam "cushion" between the head and flow generator would provide some benefit.

[0051] In another aspect, a motor can provide a heat sink to provide ability to warm patient breathing air temperature to improve breathing comfort. An additional

aspect is to be able to control the temperature based on ambient conditions, e.g., using a feedback loop. These aspects may be incorporated as part of any of the above embodiments.

[0052] While the invention has been described by way of illustrative embodiments, it is understood that the words which have been used herein are words of description, rather than words of limitation. Changes may be made without departing from the scope and spirit of the embodiments. For example, while embodiments have been described as relation to CPAP application, it is to be understood that the features described herein may also have application in the general ventilation or respiratory arts. In addition, the system can be used for children and adults of all ages.

WHAT IS CLAIMED IS:

1. A ventilator system comprising:
a mask to be placed over a wearer's face, said mask having
a shell;
a cushion provided to the shell to sealingly connect the mask to the
wearer's face and thereby form a chamber between the shell and the wearer's
face; and
an inlet port in said shell to receive a flow of breathable gas; and
an air flow generator, said air flow generator being mounted on said mask and
being capable of creating a pressure of about 2-40cm H₂O in said chamber.
2. The system of claim 1, wherein the mask is structured to cover the
wearer's nasal and oral region.
3. The system of any one of claims 1 or 2, wherein the mask is
constructed to avoid obstruction of the wearer's vision or field of view.
4. The system of any one of claims 1-3, wherein said mask is absent a
dust filter.
5. The system of any one of claims 1-4, wherein the mask is designed to
have said inlet port located in front of the wearer's oral region.
6. The system of any one of claims 1-5, wherein said air flow generator
has an air intake opening and an air outlet, said air outlet being positioned in
proximity to said air inlet port of the mask.
7. The system of claim 6, wherein a perforated screen positioned between
said air outlet and said inlet port.

8. The system of any one of claims 1-7, wherein said cushion comprises a silicone elastomer.

9. The system of any one of claims 1-8, wherein said air flow generator comprises a housing including an impeller and a motor to drive the impeller, said housing forming a contiguous surface with the shell.

10. The system of claim 9, the ventilator system further comprising a power cord and a power source, said power cord connecting said power source to said motor.

11. The system of claim 10, wherein said power source is a battery pack.

12. The system of claim 11, wherein said battery pack comprises at least one fastener to mount the battery pack to said wearer's body.

13. The system of any one of claims 1-9, further comprising a self-contained power source.

14. A ventilator system comprising:

a mask having

a shell;

a cushion provided to the shell to sealingly connect the mask to a wearer's face and thereby form a chamber between said shell and said wearer's face;

an inlet port in said shell to receive a flow of breathable gas;

an air flow generator; and

an air delivery tube not exceeding 1.5 meters in length, said air delivery tube being functionally connected to said inlet port and said air flow generator to create a

pressure of about 2-40cm H₂O in said chamber by delivery of breathable gas from said air flow generator to said inlet port.

15. The system of claim 14, wherein said air delivery tube does not exceed 1 meter in length.

16. The system of any one of claims 14 or 15, wherein the air delivery tube is low in profile and is kink resistant.

17. The system of any one of claims 14-16, wherein the mask is structured to cover the wearer's nasal and oral region.

18. The system of any one of claims 14-17, wherein the mask is constructed to avoid obstruction of the wearer's vision.

19. The system of any one of claims 14-18, wherein said mask is absent a dust filter.

20. The system of any one of claims 14-19, wherein said air flow generator is absent a dust filter.

21. The system of any one of claims 14-20, wherein the mask is designed to have said inlet port located in proximity to a wearer's oral region.

22. The system of any one of claims 14-21, wherein said cushion comprises a silicone elastomer.

23. The system of any one of claims 14-21, wherein said air flow generator comprises a housing with an impeller and a motor for driving the impeller.

24. The system of claim 23, wherein said ventilator system further comprises a power cord and a power source, said power cord connecting said power source to said motor.

25. The system of claim 24, wherein said power source is a battery pack.

26. The system of any one of claims 14-25, wherein said air flow generator comprises one or more straps or clips for mounting the air flow generator to the wearer's body.

27. The system of any one of claims 1-26, wherein said air flow generator is selectively detachable from the shell.

28. The system of claim 27, wherein the air flow generator and shell are coupled with a quick release clip.

29. The system of any one of claims 1-28, further comprising at least one sensor provided to the mask.

30. The system of claim 29, wherein the sensor is structured to provide a signal indicative of the fit of the mask.

31. The system of claim 29 or 30, wherein the sensor is structured to provide a signal indicative of leak on the basis of which the flow generator is adapted to be controlled.




FIG. 2

3/13




FIG. 3

4/13




FIG. 4

5/13




FIG. 5

6/13




FIG. 6




FIG. 7

7/13





FIG. 8

8/13



9/13




FIG. 9B





FIG. 10A

11/13



12/13




FIG. 11A

13/13




FIG. 11B

INTERNATIONAL SEARCH REPORT

International application No.

PCT/AU2004/001309

A. CLASSIFICATION OF SUBJECT MATTER

Int. Cl. 7: A61M 16/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

DWPI IPC A61M, A62B and Keywords (respiration, ventilation, breathing, CPAP, OSA, mask, integrated, mounting, combination, unitary, embedded, incorporated, attached, person, mobile, portable, wearable, worn, compressor, blower, generator, pump, motor, fan, impeller, tube, tubing, hose, hosing, conduit, length, distance, separation, reduce, shorten, minimise) and like terms

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P, X	DE 10261602 A1 (YAMAMOTO KOGAKU CO LTD) 8 July 2004 whole document	1-13, 27, 28
X	US 2003/0172930 A1 (KULLIK et al) 18 September 2003 whole document	1-13, 27-31
X	US 6435184 B1 (HO) 20 August 2002 whole document	1-13



Further documents are listed in the continuation of Box C



See patent family annex

* Special categories of cited documents:	
"A" document defining the general state of the art which is not considered to be of particular relevance	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"E" earlier application or patent but published on or after the international filing date	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"O" document referring to an oral disclosure, use, exhibition or other means	"&" document member of the same patent family
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search
13 October 2004

Date of mailing of the international search report

22 OCT 2004

Name and mailing address of the ISA/AU
AUSTRALIAN PATENT OFFICE
PO BOX 200, WODEN ACT 2606, AUSTRALIA
E-mail address: pct@ipaustralia.gov.au
Facsimile No. (02) 6285 3929

Authorized officer

SUE THOMAS

Telephone No : (02) 6283 2454

INTERNATIONAL SEARCH REPORT

International application No.

PCT/AU2004/001309

C (Continuation).

DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5372130 A (STERN et al) 13 December 1994 whole document	1-13
X	US 5303701 A (HEINS et al) 19 April 1994 whole document	1-13, 29-30
X	GB 2215216 A (SABRE SAFETY LTD) 20 September 1989 whole document	1-13, 29, 30
X	EP 0164946 A2 (RACAL SAFETY LTD) 18 December 1985 whole document	1-13, 27-31
X	US 2002/0029777 A1 (ZIMPRICH et al) 14 March 2002 whole document	14-22, 26
X	EP 0528733 B1 (INTERTECHNIQUE) 11 September 1996 whole document	14-25, 29-31
X	US 4590951 A (O'CONNER) 27 May 1986 whole document	14-26
X	EP 0066451 B1 (RACAL SAFETY LTD) 21 August 1985 whole document	14-26
X	US 4297999 A (KITRELL) 3 November 1981 whole document	14-22
X	US 4233972 A (HAUFF et al) 18 November 1980 whole document	14-26

INTERNATIONAL SEARCH REPORT

International application No.

PCT/AU2004/001309

Box No. II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a)

Box No. III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:
See extra sheet.

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☒ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
☐ No protest accompanied the payment of additional search fees.

Supplemental Box

(To be used when the space in any of Boxes I to VIII is not sufficient)

Continuation of Box No: III

The international application does not comply with the requirements of unity of invention because it does not relate to one invention or to a group of inventions so linked as to form a single general inventive concept. In coming to this conclusion the International Searching Authority has found that there are different inventions as follows:

1. Claims 1-13 relate to a ventilator system comprising a mask having a shell, a cushion, an inlet port in said shell to receive a flow of breathable gas, and an air flow generator mounted on said mask. It is considered that the air flow generator mounted on said mask comprises a first "special technical feature".
2. Claims 14-26 relate to a ventilator system comprising a mask having a shell, a cushion, an inlet port in said shell to receive a flow of breathable gas, an air flow generator, and an air delivery tube not exceeding 1.5 meters in length connected to said inlet port. It is considered that the air delivery tube not exceeding 1.5 meters comprises a second special technical feature.

Since the abovementioned groups of claims do not share any of the technical features identified, a "technical relationship" between the inventions, as defined in PCT rule 13.2 does not exist. Accordingly the international application does not relate to one invention or to a single inventive concept, a priori.

However, since the separate groups of inventions share the same classification under the IPC it is considered they could be searched together without additional effort so as to justify the requirement of payment of an additional fee.

Furthermore, although claims 27-31 are dependant of both groups of claims, the second invention is made unclear when claims 27 and 28 are appended to the second group of claims. As such, claims 27 and 28 will only be considered with the first group of claims.

INTERNATIONAL SEARCH REPORT

Information on patent family members

PCT/AU2004/001309

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent Document Cited in Search Report		Patent Family Member			
DE	10261602				
US	2003172930	DE	10210878	FR	2837108
US	6435184				
US	5372130	CA	2090741	EP	0558147
US	5303701	DE	4133235	EP	0536546
GB	2215216				
EP	0164946	AU	42753/85	DK	245185
		JP	61002878	FI	852272
US	2002029777				
EP	0528733	CA	2076408	FR	2680467
US	4590951	AU	29143/84	CA	1218579
		ES	8504469	FI	842275
		HK	8687	JP	60068869
		ZA	8404268	MY	18987
EP	0066451	AU	84215/82	GB	2099709
		US	4430995	ZA	8203655
US	4297999				
US	4233972				
Due to data integration issues this family listing may not include 10 digit Australian applications filed since May 2001.					
END OF ANNEX					